

Honeywell IntelliDoX

Automatic Instrument Management System

The IntelliDoX system combines smart docking modules and device management software to provide automated instrument management for compatible detectors, helping you drive productivity, reliability and efficiency. Place the detector in the docking module, and it automatically tests the gas detector and sensors while transferring data to the docking station.

The IntelliDoX delivers quicker bump tests for better productivity. Bump as many as five detectors in less than a minute. That means no more queues of workers waiting to test their detectors. Gang up to five IntelliDoX for even greater productivity, each module can function independently, managing fleets of detectors, all simultaneously.

Efficient when networked via Ethernet or stand-alone, transfer data with a USB drive, the IntelliDoX is the solution for easy record-keeping, to transfer bump tests, peak exposures and other gas-detection data.

Standard Package Contents

- One IntelliDoX module with a factory-installed nest for a compatible portable gas detector, a Single-Inlet Key or Multi-Inlet Key (Honeywell BW™ Ultra module only), and an attached End Plate
- Integrated retractable stand/wall mount
- Quick Reference Guide



Note: Operator's Manual and PC Configuration software available for download at www.honeywellanalytics.com.

Note: IntelliDoX enabler kit with power supply must be ordered separately. See next page for details.



Compatible Detectors:

- Honeywell BW™ Clip Series
- Honeywell BW™ Solo
- Honeywell BW™ Clip4
- Honeywell BW™ MicroClip Series
- Honeywell BW™ Ultra

GENERAL SPECIFICATIONS	
SIZE	5.4 x 14.2 x 4.3 in. / 13.8 x 36.2 x 10.9 cm (per docking module)
WEIGHT	4.2 lbs. / 1.91 kg
POWER SUPPLY	12 V / 8.33A ITE
EXTERNAL INTERFACE	1 USB port, 1 ethernet port
PUMP	Flow rate: 350 ml/min (independent pump in each module)
AUTOMATIC TESTS	FastBump Standard Bump Calibration (times dependent on instrument and configuration) Hibernation
INSTRUMENT MANAGEMENT SYSTEM	Honeywell SafetySuite Fleet Manager II, version 4.4 or higher
LCD DISPLAY COLOR CODING	Yellow "TEST", Green "PASS", Red "FAIL"
CERTIFICATIONS AND APPROVALS	 Certificate of Compliance; CSA/UL 61010-1 (3rd Ed)  EC Declaration of Conformity; EMC Directive & Low Voltage Directive
WARRANTY	Full two year warranty

Honeywell IntelliDoX Automatic Instrument Management System

ORDERING INFORMATION	
IntelliDoX Docking System	Order Number
IntelliDoX docking station for Honeywell BW® Clip Series*	DX-CLIP
IntelliDoX docking station for Honeywell BW™ Solo*	DX-SOLO
IntelliDoX docking station for Honeywell BW™ MicroClip Series*	DX-MCLP
IntelliDoX docking station for Honeywell BW™ Clip4*	DX-BWC4
IntelliDoX docking station for Honeywell BW™ Ultra*	DX-ULTRA
IntelliDoX enabler kit, NA version (North America)†	DX-ENBL-NA
IntelliDoX enabler kit, EU version (Europe)†	DX-ENBL-EU
IntelliDoX enabler kit, UK version (United Kingdom)†	DX-ENBL-UK
IntelliDoX enabler kit, AU version (Australia)†	DX-ENBL-AU

*Note: One IntelliDoX enabler kit is required for each docking system. Each docking system can support up to 5 IntelliDoX modules.

†IntelliDoX enabler kit includes power supply with region-specific AC power cord, ethernet cable, inlet (purge) filter assembly, 3 ft. / 1 m calibration gas tubing, 3 ft. / 1 m purge gas tubing, 15 ft. / 4.5 m exhaust tubing and quick connect fittings.

IntelliDoX Accessories	Order Number
IntelliDoX Mobile Case (Standard) supports 1 or 2 IntelliDoX units and two 34L cylinders. <i>IntelliDoX and Enabler Kit sold separately.</i>	DX-CASE
IntelliDoX Mobile Case (Large) supports 1 or 2 IntelliDoX units and two 58L cylinders. <i>IntelliDoX and Enabler Kit sold separately.</i>	DX-CASE1
IntelliDoX Single-Inlet Key	DX-SI-KEY
IntelliDoX Multi-Inlet Key	DX-MI-KEY
AC power supply for IntelliDoX, NA version (North America)	DX-PS-NA
AC power supply for IntelliDoX, EU version (Europe)	DX-PS-EU
AC power supply for IntelliDoX, UK version (United Kingdom)	DX-PS-UK
AC power supply for IntelliDoX, AU version (Australia)	DX-PS-AU
IntelliDoX vehicle power adaptor	DX-VPA
Demand flow regulator	REG-DF-1
Demand flow regulator for refillable cylinders, CGA connector	REG-DF-2
Demand flow regulator for disposable steel cylinders	REG-DF-3

IntelliDoX Spares & Replacements	Order Number
IntelliDoX Nest for Honeywell BW® Clip Series	DX-NEST-CLIP
IntelliDoX Nest for Honeywell BW™ Solo	DX-NEST-SOLO
IntelliDoX Nest for Honeywell BW™ MicroClip Series	DX-NEST-MCLP
IntelliDoX Nest for Honeywell BW™ Clip4	DX-NEST-BWC4
IntelliDoX Nest for Honeywell BW™ Ultra	DX-NEST-ULTRA
IntelliDoX universal latch arm (kit of 5)	DX-ARM
IntelliDoX universal end plate (kit of 5)	DX-COVER
IntelliDoX filters and hoses kit	DX-FILTERS
IntelliDoX retractable stand/wall mount (kit of 5)	DX-STAND

For more information

www.honeywellanalytics.com

Rev 3-USD | 09/12/18
© 2018 Honeywell International Inc.

Device Management with
Honeywell SafetySuite



[honeywellanalytics.com/
SafetySuite](http://honeywellanalytics.com/SafetySuite)

Honeywell