



## VMS2-54

### DC Voltage Transducer

#### Electrical Data

Input Range	0-0.01V...500V
Output	4-20mA DC
Auxiliary Power Supply ( $\pm 5\%$ )	+24V
Offset Voltage	10mV
Auxiliary Power Consumption	Voltage output $\leq 0.4W$ ; Current output(4~20mA) $\leq 0.8W$
Isolation Voltage	2500 Vdc
Overload Capacity	2 times full scale

#### Dynamic Performance Data

Accuracy Grade	0.2%
Linearity	1%
Thermal Drift	200 ppm/ $^{\circ}C$
Hysteresis Error	10mV
Response Time	300ms
Load Capacity	$\geq 2K\Omega$ (voltage output); $\leq 250\Omega$ (current output)

#### General Data

Standards	Q/BHD01-2012BH
Flame Retardancy	UL94-V0
Operating Temperature	-20 ~ +60 $^{\circ}C$
Storage Temperature	-55 ~ +65 $^{\circ}C$

## Dimensions (in mm, 1mm = 0.0394 inch)



### Mechanical Characteristics

General tolerance  $\pm 0.5\text{mm}$

## Connection Diagram





## Warranty

### Warranty Terms

With proper use and correct installation, if the product fails to work due to its own problem, SET will repair or replace the damaged product.

### Exceptions

Items are not covered under warranty:

1. Unable to provide the purchase order number and the label of the product.
2. The product is damaged by improper use or installation.
3. The sealed case of the product has been removed or the product has been repaired by user.
4. The product is damaged by the tough environment which is out of its specification.
5. Product has been out of warranty period.
6. Your demands are higher than standard or specification of SET products.

### Warranty period

We guarantee the original purchaser of our products a 24-month warranty from the date of purchase or the date of proforma invoice.