

Cellular Router - 3G UMTS/HSPA+

UR5i v2 Series



PRODUCT FEATURES

- Designed for M2M applications
- WiFi, M-BUS and Modbus TCP / Modbus RTU
- Modular design to fit application requirements
- Single or dual SIM cards for redundant backhaul
- Up to 5.7 Mbps upload to 21.1 Mbps download
- LINUX platform & advanced networking functions
- 'C' based dev environment to build user applications

3G UMTS/HSPA routers, UR5i v2 series, are used to wirelessly connect various equipment and devices via Ethernet 10/100 to the Internet or intranet. High data transfer speed of up to 21.1 Mbit/s (download) and upload speed up to 5.7 Mbit/s, make it an ideal wireless solution for traffic and security camera systems, individual computers, LAN networks, automatic teller machines (ATM) and other self-service terminals, etc.

Key features

This exceptionally fast 3G UR5i v2 wireless router is equipped with one Ethernet 10/100, one USB Host port, one binary Input/Output (I/O) port and one SIM card. To save and backup communication data, a version with 2 x SIM cards is available. A wide range of user-defined interface options further expands optional Port1 and Port2. (EX: Ethernet port 10/100, serial interface ports RS232/RS485/RS422/M-Bus or (I/O - CNT). Port2 may be equipped with serial interfaces RS232/RS485/RS422/M-Bus or (I/O - CNT). This 3G wireless router is available in a plastic or metal casing.

Configuration is done via web interface protected by password. The 3G UMTS/HSPA+ router supports creation of VPN tunnels using IPsec, OpenVPN and L2TP to ensure safe communication. Web interface provides detail statistics about router activities, signal strength, detailed log, etc. Cellular router supports functions: DHCP, NAT, NAT-T, DynDNS, NTP, VRRP, control by SMS and many other functions.

Other diagnostic functions ensuring continuous communication include automatic inspection of PPP connection offering an automatic restart feature in case of connection losses, and hardware watchdog which monitors the status of the router. With the help of a start up script window you may insert Linux scripts for various actions and, for some applications the option to create several different configurations for one 3G wireless router, profiles (maximum of 4), and the option to switch between them (for example via SMS, binary input status, etc.). Cellular wireless routers can automatically upgrade configuration and firmware from server. This allows mass reconfiguration of multiple routers at one time.

ORDERING INFORMATION

MODEL NUMBER	ETH 10/100	USB	SIM	RS232	RS485/ RS422	M-BUS	I/O	I/O (CNT)	WIFI
UR5i v2B Set	1	1	1				1		
UR5i v2B ETH Set	2	1	1				1		
UR5i v2B RS232 Set	1	1	1	1			1		
UR5i v2B RS485/422 Set	1	1	1		1		1		
UR5i v2B M-Bus Set	1	1	1			1	1		
UR5i v2B CNT Set	1	1	1				1	1	
UR5i v2F Set	1	1	2				1		
UR5i v2F ETH Set	2	1	2				1		
UR5i v2F RS232 Set	1	1	2	1			1		
UR5i v2F RS485/422 Set	1	1	2		1		1		
UR5i v2F M-Bus Set	1	1	2			1	1		
UR5i v2F CNT Set	1	1	2				1	1	
UR5i v2F WIFI Set	1	1	2				1		1
UR5i v2F SWITCH Set	3	1	2				1		
SL	Router metal casing (sample ER75i v2B SL)								

Europe, Middle East, Africa, Asia, South America, Latin America.
Check with your local distributor for availability and options.

ACCESSORIES

MDR-40-24	24VDC, 20W, 1 A power supply
C5UMB3FBG	Category 5E UTP 3 f/1 m - Beige
C5UMB10FBL	Category 5E 10 ft/ 3 m - Blue

SELECTED APPLICATIONS

Transportation and security
IT and communication
Self-service terminals
Energy and power industry
Metrology, alarm and warning systems