



OPM, SI (SOC)

Fiber Optic Power Meter SI, (SOC)

Cat No: 52058723

UPC No: 783310000259

Description

- Easy to use - three button control all functions
- Loss measurements in (dB)
- Power measurements in (dBm)
- Snap on connector interface adapts to FC, SC and ST connectors
- Long battery life
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

Specifications

- Accuracy : +/- 0.25 DB
- Calibration Wavelengths : 635, 780 And 850 nm
- Connector interface : SOC
- Detector Type : 3 X 3.5 MM Silicon
- Dimensions : 2.8 (7.2 CM) Length X 1.4 (3.5 CM) Width X 5.6 (14.2 CM) Height
- Humidity : 0 To 95 PCT Non-Condensing
- Linearity : 3 To -3 dBm (+/- 0.5 db), -3 To -50 dBm (+/- 0.05 db), -50 To -60 dBm (+/- 0.5 db)
- Operating Temperature : -15 To 55°C
- Power Range : 3 To -60
- Power Supply : (2) 1.5 V AA Size Battery
- Resolution : 0.01
- Standard :
 - CE - EN61010
 - EN50081-1: 1992
 - EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4
- Storage Temperature : -35 To 70°C
- Sub Brand : fiberTOOLS
- Type : XL Series, Fiber Optic
- Weight : 241 G (8.5 OZ)